



"Easyflex" Level Mounts for Vibration/Shock/Noise Isolation

Here's All You Have To Do

- Move machine into place.
- Raise Machine
- Attach Mounts and lower machine. Adjust leveling screws until machine is level.



"Easyflex" Mounts Take only a Few Minutes to Install.

Economy & Advantages

- "Easy Flex" Level-Mounts require no expense for floor preparation, bolts, anchor plates, masonary Drilling and re-cementing.
- Built-in levelling adjustment saves time, labour and money.
- Mounts are practically indestructible and match the life of mounted machine.
- No Foundation * Flexible Production Lines * Shock & Vibration Isolation * Reduced Maintenance & Less Noise
- Available in Oil Resistant Nitrile Rubber.

Size	Load Capacity	Standard Bolt Size	Length inch/mm
Type : SC - 12	(Heavy Duty)		
EFLM-090/SC-12	900 - 1350	1/2"/M 12	4"/100mm
EFLM-110/SC-12	1350 - 2000	5/8"/M 16	5"/125mm
EFLM-128/SC-12	1800 - 2700	5/8"/M 16	5"/125mm
EFLM-156/SC-12	2700 - 4050	3/4"/M 20	6"/150mm
EFLM-180/SC-12	3600 - 5400	3/4"/M 20	6"/150mm
EFLM-210/SC-12	4900 - 7300	1"/M 24	8"/200mm
EFLM-240/SC-12	6400 - 9600	1"/M 24	8"/200mm
EFLM-300/SC-12	10000 - 15000	As per requirement	
EFLM-400/SC-12	17600 - 26700	As per requirement	

Note: To be used with Load Factor