

### Typical Application

The 6 feet of the standard EFSRF range are a practical and versatile support solution for pipe work and cable trays. They can also be used for smaller outdoor condensing units or air source heat pump installations. The feet have a 41 mm x 21 mm 'bonded' in channel, which is recessed into the top face allowing you to use standard strut fixings to secure your services to the feet.

Our EFSFR range are made from Recycled SBR rubber, making them eco friendly. They also have the added advantage of vibration and noise absorption which makes them the perfect product for roof or ground level installation.



Part No	Model	Length (mm)	Width (mm)	Height (mm)	Max Loading Per Foot (kg)
EF-4025	EFSFR250	250	180	95	160
EF-4040	EFSFR400	400	180	95	240
EF-4060	EFSFR600	600	180	95	450
EF-4010	EFSFR1000	1000	180	95	645
EF-4525	EFSFR250 Low	250	130	50	160
EF-4540	EFSFR400 Low	400	130	50	240

Part No	Model	Length (mm)	Width (mm)	Height (mm)	Max Loading Per Foot (kg)
EF-1560	EFSFR600 High Block	600	130	150	450
EF-1512	EFSFR1200 High Block	1200	130	150	645

### Material Specification

SBR-Recycled Rubber. Bound using a ratio of high quality moisture curing Polyurethane Pre-Polymer.  
BS7188:1989+A2:2009 and BS EN1176-7:2008

### Metal Profile

Aluminium strut 41 mm x 21 mm profile compatible with strut fixings.

### Working Conditions

Suitable for internal or external applications in temperatures between -40 C to +80 C. BSEN60068-2-14

