





AIR HANDLING UNITS

AXIAL FANS

BLOWERS

AIR POLLUTION SYSTEMS

INDUSTRIAL DUCTING

Materials: PVC | NEOPRENE | SILICONE

Fabric Sizes: 150.200.300.350.1000.1500mm width

FDC Sizes: 45x60|100|150.70x100|150

FLEXIBLE CONNECTIONS

FABRIC

FLEXIBLE DUCT CONNECTORS

- Fabric Rolls
- Fire Rated Fabric
- Fabrics with GI Strip
- Fibreglass Insulated Fabric
- 2 Ply Fabrics | Double Canvas
- Factory Fabricated Flanged Connectors



Flexible Duct Connectors

Air Duct installation connected with Fans, Blowers and Air Handling Units should be installed with Flexible Canvas connections to eliminate transfer of noise and vibration throughout the entire ducting.



- NFPA Approved
- UL Listed Fabrics
- Fire Rated & Retardant
- Available in 2 Ply and Fibre Glass Insulation
- Suitable for Temperature ranges upto 400°C
- Customised to Round, Rectangular and Square connectors

FLEXIBLE CONNECTIONS
SILICONE / NEOPRENE / PVC | FABRIC WITH GI STRIP



Temperature Ratings	
ROBG / PVC	-30.c / + 70.c
NEOPRENE	-20.c / + 100.c
SILICONE	-50.c / +200.c

Available as **Fabric Rolls**, **Fabric with GI End Strips** and factory
fabricated **Flanged Connectors**,
to isolate transmission of noise
and vibrations.



FLEXIBLE CONNECTIONS

Box Quantity FDC: 25RMT | Box Quantity Fabric: 50RMT

Square / Rectangular

FLANGED FABRIC DUCT CONNECTOR





Round

FLANGED FABRIC DUCT CONNECTOR





Round to Rectangular

FABRIC





FLEXIBLE CONNECTIONS
SPECIAL APPLICATIONS

Round to Rectangular

FABRIC







FLEXIBLE CONNECTIONS
ROUND TO RECTANGULAR DUCT CONNECTORS | SIZE 1400 to 1350 DIA X 300mm OAL